

■Flash functions available with cameras when used with an external Speedlight

COOLPIX P7100, P7000, P6000

			Speedlight compatible with CLS											Speedlight incompatible with CLS					
			SB-5000	SB-900 SB-910	SB-800	SB-700	SB-600	SB-500	SU-800		SB-R200	SB-400	SB-300	SB-80DX SB-28DX	SB-50DX	SB-28 SB-26 SB-25 SB-24	SB-30, SB-27 SB-22S, SB-22 SB-20, SB-16B SB-15	SB-23 SB-29 SB-21B SB-29S	
									Commander	Close up									
Single flash	i-TTL	i-TTL balanced fill-flash *1	-	○	○	○	○	○	-	-	-	○	○	—	—	—	—	—	
		Standard i-TTL	○*2	○*2	○*2	○	○*2	○	-	-	-	○	○	—	—	—	—	—	
	TTL	TTL flash control for	-	-	-	-	-	-	-	-	-	-	-	-	-	—	—	—	
		Speedlights incompatible with CLS	-	-	-	-	-	-	-	-	-	-	-	-	-	—	—	—	
	AA	Auto aperture flash	○	○	○	-	-	-	-	-	-	-	-	-	—	—	—	—	
	A	Non-TTL auto flash	-	○	○	-	-	-	-	-	-	-	-	○	—	○	○	—	
	GN	Distance-priority manual flash	○	○	○	○	-	-	-	-	-	-	-	○	—	—	—	—	
	M	Manual flash	○	○	○	○	○	-	-	-	-	-	-	○	○	○	○	○	
RPT	Repeating flash	○	○	○	-	-	-	-	-	-	-	-	—	—	—	—	—		
Optical AWL	Master	Setting	Commander function	○	○	○	○	-	-	○	○	-	-	-					
			Controllable group	A	A	A	A	-	A/B	A	A	-	-	-					
			Mode setting	A/B/C	A/B/C	A/B/C	A/B	-	A/B	A/B/C	A/B: Common C: M fix	-	-	-					
		Mode setting for remote	Same as master	Same as master	Same as master	Same as master	-	Master+AA	Same as SB-800	Same as SB-700	-	-	-						
		i-TTL	i-TTL flash control	-	-	-	-	-	-	-	-	-	-						
		[A:B]	Quick wireless control	-	-	-	-	-	-	-	-	-	-						
		AA	Auto aperture flash	-	-	-	-	-	-	-	-	-	-						
		A	Non-TTL auto flash	-	-	-	-	-	-	-	-	-	-						
	M	Manual flash	-	-	-	-	-	-	-	-	-	-							
	RPT	Repeating flash	-	-	-	-	-	-	-	-	-	-							
	Remote	i-TTL	i-TTL flash control	○	○	○	○	○	○	-	-	○	-	-					
		[A:B]	Quick wireless control	-	-	-	-	-	-	-	-	-	-						
		AA	Auto aperture flash	○	○	○	-	-	-	-	-	-	-						
		A	Non-TTL auto flash	○	○	○	-	-	-	-	-	-	-						
M		Manual flash	○	○	○	○	○	○	-	-	○	-	-						
RPT		Repeating flash	○	○	○	○	○	○	-	-	-	-	-						
Color Information Communication (flash)			-	-	-	-	-	-	-	-	-	-	-						
Color Information Communication (LED light)			-	-	-	-	-	-	-	-	-	-	-						
Auto FP high-speed sync *6			-	-	-	-	-	-	-	-	-	-	-						
FV lock *7			-	-	-	-	-	-	-	-	-	-	-						
AF-assist for multi-area AF			-	-	-	-	-	-	-	-	-	-	-						
Modeling illumination using camera control			-	-	-	-	-	-	-	-	-	-	-						
Modeling illumination using flash control			○	○	○	-	-	-	Signal only	-	Remote only	-	-						
Red-eye reduction			○	○	○	○	○	○	-	-	-	○	-						
Unified flash control			-	-	-	-	-	-	-	-	-	-	-						
Flash mode setting from camera			-	-	-	-	-	-	-	-	-	-	-						
Scenes/special effects flash control			-	-	-	-	-	-	-	-	-	-	-						
Flash unit firmware update via camera			-	-	-	-	-	-	-	-	-	-	-						
SU-4	Master	AA	Auto aperture flash	○	○	-	-	-	-	-	-	-	-						
		A	Non-TTL auto flash	○	○	○	-	-	-	-	-	-	-						
		GN	Distance-priority manual flash	○	○	○	-	-	-	-	-	-	-						
		M	Manual	○	○	○	-	-	-	-	-	-	-						
	Remote	AUTO	Auto	○	○	○	○	-	-	-	-	-	-						
		M	Manual	○	○	○	○	-	-	-	-	-	-						

*1 Not available with spot metering.

*2 Can be also selected with flash unit.

*3 AA/Mode A selection preformed on flash unit using custom settings. Mode A will be selected when a non-CPU lens is used.

*4 Can only be selected using camera Flash Control option.

*5 Mode A will be selected when a non-CPU lens is mounted, regardless of mode selected using flash unit's custom settings.

*6 Available only in i-TTL, AA, A, GN and M mode.

*7 Available only in i-TTL, AA and A.

Cannot be configured	—	Not supported by camera
	Text entered	Not supported by camera, but flash functions are indicated
Can be configured	—	Function not available with flash unit
	○	Available
	Text entered	Available; additional information noted